

# VANTEL-29-NE TRANSIT

## Telescopic Aerial Device

**PLATFORM CAPACITY:** Up to 350 lbs. (159 kg)

**WORKING HEIGHT:** 33 ft. 10 in. (10.3 m)

**HORIZONTAL REACH:** 22 ft. 7 in. (6.88 m)



# VANTEL-29-NE TRANSIT



## Telescopic Aerial Device

### GENERAL SPECIFICATIONS

Standard Horizontal Reach  
Horizontal Reach w/ Positioner  
Standard Platform Capacity  
Outer Boom Travel  
Inner Boom Extension  
Height to Bottom of Platform  
Working Height  
Stowed Travel Height  
Weight of Lift W/ Mounting Hardware  
Operating Pressure  
Flow Rate  
Filtration  
System Type

### VANTEL-29-NE TRANSIT

22 ft. 7 in. (6.88 m)  
23 ft. 1 in. (7 m)  
300 lbs. (136 kg)  
-8° to +80°  
116 in. (2.95 m)  
28 ft. 10 in. (8.79 m)  
33 ft. 10 in. (10.3 m)  
9 ft. 6 in. (2.9 m)  
1530 lbs. (694 kg) <sup>2</sup>  
2250 PSI (158 KG/CM )  
2 GPM (8 lpm)  
10 micron return/ 100 mesh suction  
Open Center

#### OPTIONS:

- EMERGENCY LOWERING
- 4 IN TALLER PEDESTAL AVAILABLE
- 2-SPEED CONTROL SYSTEM
- VARIABLE SPEED CONTROL SYSTEM
- BACK UP PUMP
- PNEUMATIC CIRCUIT(S) TO THE PLATFORM
- VARIOUS PLATFORMS, DOORS AND COVERS
- BUMPER EXTENSIONS
- 120 VOLT RECEPTACLE AT PLATFORM
- MANUAL PLATFORM POSITIONER
- ELECTRIC DRIVE

#### NOTE:

1. Specifications might vary without prior notification
2. Required GVWR can vary significantly with chassis, lift mounting location, service body, accessories, and desired payload

